

WHAT IS CLAIMED IS:

1. A developing apparatus comprising:

a toner carrying member for carrying toner to
a developing zone where said developing apparatus
5 faces to an image bearing member;

bias voltage applying means for applying to
said toner carrying member a developing bias voltage
for developing an electrostatic latent image formed on
the image bearing member, wherein said developing bias
10 voltage is in the form of a DC voltage biased with an
AC voltage said;

wherein when a developing operation stops,
rotation of said toner carrying member is stopped
while rotating the image bearing member electrically
15 charged, and then, the AC voltage is applied to said
toner carrying member for a predetermined period, and
thereafter, the AC voltage is stopped in a condition
in which regular-charge toner is being urged from said
toner carrying member toward the image bearing member.

2. An apparatus according to Claim 1, wherein
the AC voltage crosses with a charged potential of the
image bearing member.

3. An apparatus according to Claim 2, wherein
said period is not less than 50msec.

4. An apparatus according to Claim 1-3, wherein the DC voltage is stopped substantially simultaneously with the DC voltage.

5 5. An apparatus according to Claim 1, wherein
said developing bias voltage comprises a first peak
voltage for forming a substantially constant electric
field for urging the regular-charge toner from said
toner carrying member toward the image bearing member,
10 and a second peak voltage for forming a substantially
constant electric field for urging the regular-charge
toner from the image bearing member toward said toner
carrying member, wherein said AC voltage is stopped
when said first peak voltage is applied.

15 6. An apparatus according to Claim 1, wherein a
charging polarity of the image bearing member is the
same as a charging polarity of the regular-charge
toner.

20 7. An apparatus according to Claim 1, wherein
said toner carrying member is a cylindrical sleeve.